## AUTEL VEHICLE DIAGNOSTIC TOOLS

#### Autel MaxiSys MS906, 906TS, MaxiSysPro, MaxiSys Elite



MaxiSYS Elite

Automotive Diagnostic	MaxiSYS PRO/ 906TS	MaxiSYS 908/908 PRO	MaxiSYS Elite
& Analysis Systems	#AUL-MS906 / 906TS	#AUL-MS908/908PRO	#AUL-MD808
CPU & Memory	Samsung Exynos 6-Core	Samsung Exynos A9	NVIDA Tegra 4
	32GB	Quad-Core 1.4GHz, 32GB	Quad-Core 1.8Ghz, 32GB
Touch Screen	8" 1024*768 LED	9.7" 1024*769 LED	9.7" 2048*1536 Retina LCD
Connectivity	USB2/Wi-Fi/Bluetooth for 906TS	USB2/Wi-Fi/Bluetooth	USB2/Wi-Fi/Bluetooth
Internal Battery			
Camera (Rear)	8 Megapixel/AF/Flash	5 Megapixel/AF/Flash	8 Megapixel/AF/Flash
Wireless Bluetooth VCI	optional	(uses J2534 for 908 Pro)	(uses J2534)
Optional Lab Scope and/or			
Optional Video-Scope			
OEM-Level Coverage for			
Domestic, Asian & Euro		•	
Auto VIN Technology			
MaxiFix Cloud-Based			
Information System			
ECU Coding		Advanced	Advanced
ECU Flash Programming	Optional with MaxiFlash Kit		2x faster
Printing of Recorded Data			
1996-2001 Connector kit	Complete Connector Kit	Complete Connector Kit	Complete Connector Kit
J2534 Hardware	Optional	Optional / Included	
Software Updates	1 Year Free	1 Year Free	1 Year Free
Price	\$1795/ \$2395	\$2595/\$3495	\$3995

#### **MaxiTPMS TS508**

**Tire Pressure Sensor Diagnostic Tool** 

Tool with 8 Programmable MX-Sensors

- Activate & Relearn All Known Sensors
- Read Sensor ID, Temperature & Pressure
- Read Battery Power Level Condition
- Sensor Position Relearn
- 4 Sensor Programming Options
- Copy by Activation/Manual Input/OBD
- Auto Create 1-16 Sensors
- Read & Clear DTCs from ECU

#### MaxiDiag MD808

- One tool can do it all-Reads and clear (engine, transmission, ABS and airbag)
- Support EPB, SAS & Oil Reset Service
- Turn off warning lights
  Supports all 10 test modes of latest J1979 OBD II test specs, including Read Codes, Erase Codes, Live Data, Freeze Frame I/M Readiness, O2 Monitoring Test, On-Board Mon. Test
- Component Test and Vehicle Information



0 ()

(;

\$395

\$749

**MaxiTPMS TS608** 

Besides all functions of TS508, TS608 Also includes All systems Diagnostics

- Read/Clear codes for all available electronic systems
- Turn off warning lights;
- Display live data in text, graph & analog for easy data review

Supports all 10 test modes of the latest J1979 OBD II test specs

Enhanced OBD II Mode 6.

433MHz

• Enhanced OBD II Mode 6

• Includes all European, Asian &

• Free Software Upgrade

Data graphing

• OBD II code tips guide technicians to

• One year free update on the internet.

Programmable TPMS Sensors with Interchangeable Rubber Valve Stems 100% ID cloneable, no relearn required

Part#	Description
AUL-MXSENSOR315R	315MHz Sensor with Rubber Stem
AUL-MXSENSOR433R	433 MHz Sensor with Ruuber Stem
	state and the second second

315MHz



P: 1844-PROTEC9 (1844-776-8329) or 905-569-8878

For more information, please visit our website:

Prices are subject to change without notice.

Page 1

Price **S45 S45** 



## LAUNCH VEHICLE DIAGNOSTIC TOOLS



#### ScanPad X431 Pro and Pro 3 Android Scan Tool Tablet

The ScanPad X431 Pro and Pro 3 is a robust, drop-tested Android based scan tool with an 8 inch and 10.1 inch High Resolution Capacitive Touch Screen.

- Featuring an open AndriodTM operating system for a true table experience – install third party apps and software!
- Class-1 Bluetooth 4.0 Connector for optimum wireless connectivity
   Launch next generation software suite: OE-Level access
- to Asian, European and Domestic applications for module coding, resets, relearns & bidirectional capabilities
- Built-in customer management software and link to LAUNCH online user community
- Auto-ID all available vehicle systems and modules
- One-Click Wi-Fi software updates
- One Year Warranty and One Year Free update

#### X431 Pro **\$1795** X431 Pro 3 **\$2595** Includes 1 Year warranty and 1 year free update

#### X431 PAD II A (Enhanced) Android Scan Tool Tablet

The PADII A is a robust, drop-tested and waterproof Android based scan tool tablet with a 10.1 inch ultra-high resolution IPS touch screen.

- Features vast vehicle coverage, powerful special test functions, ultra-fast live data and graphing, along with module-coding capabilities.
- New revolutionary Customer Remote Diagnostics capability called "Golo" that allows the shop owner and technician to remotely analyze customer vehicle data outside the shop, even thousands of miles away!
- A built-in customer management system and online user community link further extends the utility and efficiency of the PADII.



X431 PADII A

Includes 1 Year warranty and 1 year free update

#### **CReader Pro 229**

- Android Based, 5 inch high resolution touch screen
- WiFi enabled for Web Browsing
- Graph multiple PIDs of Live data
- Access All Vehicle Systems for Reading and Clearing Codes & Live Data
- Performs The Following:
   Oil Light Resets, Electronic Parking Brake (Retract Reset), Steering Angle Reset, Battery Registration
- GOLO ready! Remove diagnostics and telematics with optional GOLO connector



#### CRP123 Premium / CRP129 Premium

The CRP123 Premium contains:

- Enhanced manufacturer specific Domestic,
- Asian & European coverage for technicians to diagnose Engine, Transmission,
- ABS and Airbag (SRS) systems.
  In addition, the CRP129 also includes Electronic Parking Brake (EPB) release
  Steering Angle Sensor (SAS) and Oil Service Light resets. Graph, Record and Play Back crucial data to more efficiently diagnose driveability issues.
- View Engine, ABS, SRS along with A/T enhanced data.
   Includes 1 Year warranty.



CRP123 Premium **\$399** CRP129 Premium **\$549** 

#### Millennium 90

Multi-purpose code reader provides 10 OBDII / EOBD diagnostic modes, Plus oil reset, brake bleeding, EPB, BMS, DPF and SAS reset, Live data stream reading, ABS and SRS diagnosis



#### TSAP-1 Tire Sensor Activation / Programming tool

- Check Tire Pressures in seconds
  Displays all available sensor data (ID, PSI, MHz, Tire Temp, Battery Life)
- One tool programs most aftermarket universal sensors
   Intuitive step-by-step instructions for sensor programming
   Provides vehicle selection via MMY look-up
- Replacement TPM sensor part number look-up
- Can be used in conjunction with scan tools
- 2 year Software updates and 2 year warranty



## FCAR HEAVY DUTY AND PASSENGER VEHICLE DIAGNOSTIC TOOLS

#### FCAR F7S-G Heavy Duty Trucks and All Passenger Vehicles

FCAR F7S-G is an all-in-one wireless tablet scanner designed to be ONE tool that any service professional will need, from car, truck or HD equipment.

- 10.1 "HD Android tablet, Quad-core 1.2Ghz Processor, built-in WiFi and Bluetooth
- Online technical information and wiring diagram.
- OE Level scanner coverage including both diesel and gasoline vehicle (12V-24V)
- Design to connect all kinds of vehicle sockets.
- All-in-one automotive diagnostic system covering passenger & light commercial vehicles, heavy duty trucks and off-road equipment.
- VIN Automatic detection for passenger vehicles.
- Read DTC, Clear DTC, Engine Models, ECU information, System Parameter Number, Data Stream, Cylinder Test, Compression Test, Bi-Directional Injector Test, Actuation Test, Key Programming, Service Reset, Adaptations, Maintenance Help, DPF Regeneration, etc.

FCAR F5-G Heavy Duty Trucks and All Passenger Vehicles scanner also available (Printer is Optional)





F3S-N One Year Warranty & **Two Years Free Update!** 

#### FCAR F3S-N Heavy Duty Trucks and American Vehicles

0,

FCAR F3S-N Truck Pro is professional diagnostic scan tool for North American Heavy duty, super duty and light duty trucks. It has covered most heavy duty on-highway trucks and off-highway utility vehicles for testing most electronic, engine, transmission ABS and Airbag modules with bi-directional functions. Scanner Coverage:

One Year Warranty & Two Years Free Update!

 HD Diesel Engines Cummins, Detroit, Caterpillar and more.

Domestic HD Trucks: Caterpillar, Freightliner, International, Kenworth, Peterbilt, Serling, LaFrance, Autocar, Pierce, Bobcat, John Deere. Imported HD Trucks: Fuso, Hino, Isuzu, Volvo, Mack, Mercedes, Man, Lveco.

Super Duty and Light Duty Trucks or Gasoline Pickup: Ford F Series, Dodge RAM, GMC, Chevrolet Silverado, Spinter, Suburtan etc..

• Extra coverage: all Ford, GM, Chrysler, Dodge passenger vehicles Including connectors: OBD 16, Diesel 6, Diesel 9 (Cummins 9 pin), CAT 9.

One Year Warranty & Two Years Free Update!

#### FCAR F6 Plus Passenger and Light Commercial Vehicles

F6 Plus, Android based all-in-one smart diagnostic tool for all European, Asian and American Cars with bi-directional capabilities.

• 8" IP67 Android tablet, water and oil proof, built-in WiFi & Bluetooth.

Basic functions: read/clear DTCs, read live data and actuation Test.

Special functions: ABS exhaust, DPF, ECU reset, EPB, lamp adaption, SAS, service reset, smart key program, SRS reset, suspension, throttle reset, TPMS, injector and cylinder test, etc. Diagram wiring, technical information, diagnostic solutions & maintenance services.

\$499

Automatically identify vehicles and systems.

One key update/recognition/feedback/Remote support.

## FCAR F506 Heavy Duty Code Reader

F506 is a Professional Heavy Duty Code Reader with Extensive International, Hino, Isuzu & UD trucks Coverage and Generic OBD II

- Works with all 1996 and newer vehicles (OBDII and CAN) and standard protocols of heavy duty Trucks (J1939 and J1708)
- More coverage, also covers Hino, Mitsubishi Fuso, Isuzu and UD commercial vehicles.
- Access Engine, Transmission, ABS, Brakes, Instrument clusters.
- Read and clear diagnostic trouble codes and view live data.
- Includes OBD 16 and Diesel 6 and 9 pin connectors.
- Provides on screen DTC definitions for heavy-duty standard codes.

Includes 1 Year Warranty 8 Free Update

#### A/C MACHINE, TRANSMISSION FLUID CHANGER, SMOKE MACHINE & BATTERY TESTER

#### A/C-400 Fully Automatic A/C Service Station for R134yf Refrigerant

- Automatic Recovery/Vacuum Oil Injection /Recharge
  - Comprehensive Vehicle A/C Capacity Database
  - Automatic Protection Program and Audible Alarms
  - LCD Screen & Built in Thermal Printer



AC-600

## A/C-600 Fully Automatic A/C Service Station for HF01234yf Refrigerant

- Automatic Recovery/Vacuum Oil Injection /Recharge
   Comprehensive Vehicle A/C Capacity Database
- Automatic Protection Program and Audible Alarms
   LCD Screen & Built in Thermal Printer
- A/C-600 Powerful Vacuum Pump & Ventilation System ( do not require spark to start, more safety)

#### Also available:

- A/C-500 for Truck R134A Refrigerant with UV Dye Leak Detection Kit and Flush Function \$3495
- A/C-800 for Coach/Bus R134A Refrigerant with 30L Large Tank and Vacuum Leak Test \$4995

#### X-SonicClean BT Injector Diagnostics and Cleaner

- Spray Pattern Testing & Evaluation
- Injector Flow & Volume Test
- Ultrasonic Cleaning & Auto Test
- Injector Leak Down Test
- Injector "Reverse Flush" Cleaning



## ATF-102 Fully Automatic Transmission Fluid Changer

- Auto Fluid Exchange
- Fluid Level Adjustment
- Automatic Discharging of Used Fluid
- Auto Fluid Flow Direction Sensor
- Transmission System Cleaning

ATF-102

#### ALL-300 Car Smoke Machine ALL-300HD Truck Smoke Machine

- EVAP Leak Test
  Exhaust Leak Test
  Under Dash Test
  Manifold Leak Test
  Vacuum Leak Test
- Built in Air Compressor
  Smoke Works with mineral oil (baby oil)
  Includes 1 Year Warranty
  All-300HD Works for Heavy Duty Trucks





ALL-300HD



#### BAT PLUS Battery Tester

Battery Test

- Grounding Test
- Starter Test
- Alternator Test
- Test all 12 Volt Batteries
- Compatible with CCA, SAE, DIN, JIS, IEC, EN and CA
- Includes 1 Year Warranty, Built In Thermal Printer.





## TOOLS CABINET, WASTE OIL DRAINER AND HIGH TRANSMISSION JACK







TB-C700 7 Drawers Tool Cabinet

Model	TB-C310	TB-C600	TB-C700
New weight	11KG (24LB)	60KG (132LB)	64KG (141LB)
Gross weight	12KG (26Lb)	62.5KG (138Lb)	66.5KG (147Lb)
Package Size	78cm*66cm*35cm	88cm*83cm*52cm	88cm*83cm*52cm
Product Size	31 "H*26"L*14"W	35 "H*32"L*20"W	35″H*32″L*20″W

# HC-2085 and HC-2285 Oil Drainer & Extractor Specifications:

Tank Capacity (Liter/US Gallon)	3 137/171	3 167/211
Air Inlet pressure (Bar/Psi)	6~8/87~116	6~8 / 87~116
Air Inlet connection (Inch)	1/4"	1/4"
Vacuum Degree (Bar)	-1~0	-1~0
Air pressure for oil discharge (Bar/Psi)	0.7~1/10~15	0.7~1/10~15
Oil Temperature range ( $^{\circ}\mathrm{C}$ )	40~60	40~60
Draining Hose (dia.@Length)	G1/2*1.5m	G1/2*2.0m
Connection Bowl Capacity (Liter/US Gallon)	3 17/21	3 17/21
Connection Bowl Diameter (mm)	400	400
Maximum Height (mm)	1650	1680
Minimum Height (mm)	1025	1040
Optional Extension Funnel Diameter (mm)	560	560
Gross Weight/Net weight (Kgs)	166/191	211/245
Dimension (mm)	470* 440* 940*	550* 430* 980*





# TJ-90103 and TJ-90104 High Transmission Jack Specifications:

Model	TJ-90103	TJ-90104
Lifting weight	0.5 Tons/1102 lbs	0.5 Tons/1102 lbs
Min. height	870mm/34.3"	870mm/34.3"
Max. height	1800mm/70.9"	1750mm/68.9"
1st stage lift	465mm/18.3"	450mm/17.7"
2 <sup>nd</sup> stage lift	465mm/18.3"	450mm/17.7"
Net weight	80kg/176lbs	60kg/132lbs
Gross weight	86kg/189lbs	68kg/150lbs

## TIRE CHANGERS



## Tire Changers

Model #	TC-411	TC-412	TC-412A	TC-512A
Description	Swing arm tire changer without bead blaster	Swing arm tire changer with bead blaster	Swing arm tire changer with bead blaster and left assist arm assembly	Tilt back tire changer with bead blaster and right assist arm assembly
Power supply	110V/60Hz, single phase, 1HP Motor	110V/60Hz,single phase, 1.5HP Motor (CSA)	110V/60Hz,single phase, 1.5HP Motor (CSA)	110V/60Hz,single phase, 1.5HP Motor (CSA)
Air Supply	8-12bar (0.8-1.2Mpa)	8-12bar (0.8-1.2Mpa)	8-12bar (0.8-1.2Mpa)	8-12bar (0.8-1.2Mpa)
Rim Clamping (External)	10"-22"	12"-26"	12-26"	12"-26"
Rim Clamping (Internal) Beed Braker Force	12"-24" 4000LB (2000KG)	14"-28" 5500LB (2500KG)	14"-28" 5500LB (2500KG)	14"-28" 5500LB (2500KG)
Max. Wheel diameter Max. Wheel width	37"(950mm) 13"(330mm)	43"(1100mm) 15"(381mm)	43"(1100mm) 15"(381mm)	43"(1100mm) 15"(381mm)
Noise	<70dB	<70dB	<70dB	<70dB
N.W/G.W	424Lb/513Lb (193Kg/233Kg)	550Lb/675Lb (250Kg/307Kg)	585Lb/705Lb (265Kg/320kg)	685Lb/779Lb (299Kg/354kg)
Packing Size	980*760*970(mm)	1140*950*980(mm)	1140*950*980(mm)	980*760*980(mm)
Price	\$1695	\$1995	\$2395	\$2995

## Combo Specials:



TC-411 + WB-511 **\$3195** *SAVE* **\$500** 



TC-412A + WB-511 **\$3895** *SAVE* **\$500** 



TC-512A + WB-511 **\$4495** *SAVE* **\$500** 

## TIRE CHANGERS



## Low Profile Tire Changers

Model #	TC-512B	TC-513A	TC-612A	TC-612B
Description	Tilt back tire changer with bead blaster and right assist arm assembly	Tilt back tire changer with bead blaster and right assist arm assembly	Swing arm tire changer with bead blaster and right assist arm assembly	Swing arm tire changer with bead blaster & dual assist arm assembly
Power supply	110V/60Hz, single phase, 1.5HP Motor (CSA )	110V/60Hz, single phase 1.5HP Motor	110V/60Hz, single phase, 1.5HP Motor (CSA approved)	110V/60Hz, single phase, 1.5HP Motor (CSA approved)
Air Supply	8-12bar (0.8-1.2Mpa)	8-12bar (0.8-1.2Mpa)	8-12bar (0.8-1.2Mpa)	8-12bar (0.8-1.2Mpa)
Rim Clamping (External)	12"-26"	12"-24"	12"-26"	12"-26"
Rim Clamping (Internal) Beed braker force	14"-28" 5500LB (2500KG)	10"-21" 5500LB (2500KG)	14"-28" 5500LB (2500KG)	14"-28" 5500LB (2500KG)
Max. Wheel diameter	43"(1100mm)	39"(1000mm)	43"(1100mm)	43"(1100mm)
Max. Wheel width	15"(381mm)	14"(355mm)	13"(330mm)	15"(381mm)
Noise	<70dB	<70dB	<70dB	<70dB
N.W/G.W	685Lb/779Lb (299Kg/354kg)	607Lb/684Lb (276Kg/311kg)	704Lb/825Lb (320Kg/375Kg)	704Lb/825Lb (320Kg/375Kg)
Packing Size	980*760*980(mm)	960*760*1050(mm)	1140*950*980(mm)	1140*950*980(mm)
Price	\$3195	\$3095	\$3095	\$3495

## **Combo Specials:**



TC-513A + WB-611 **\$4995** *SAVE* **\$500** 



TC-612A + WB-611 **\$4995** *SAVE* **\$500** 



TC-612B + WB-514 **\$5995** *SAVE* **\$500** 



TC-512B + WB-514 **\$5695** SAVE **\$500** 

## TIRE CHANGERS

## New Model Tire Changers



Model #	TC-1291IT	TC-1298IT	TC-1227IT	TC-1297IT
Description	Tilt arm tire changer with bead blaster and left assist arm assembly	Swing arm tire changer with bead blaster and assist on both sides	Tilt arm tire changer with bead blaster and left assist arm assembly	Swing arm tire changer with bead blaster and left assist arm assembly
Power supply	110V/60Hz, single phase, 1.5 HP Motor	110V/60Hz, single phase, 1.5HP Motor	110V/60Hz, single phase, 1.5HP Motor	110V/60Hz, singlephase, 1.5HP Motor
Air Supply	8-10bar (116-145PSI)	8-10bar (116-145PSI)	8-10bar (116-145PSI)	8-10bar (116-145PSI)
Rim Clamping (External)	12"-23"	12"-26"	12"-24"	12-26"
Rim Clamping (Internal)	14"-26"	14"-28"	10"-21"	14"-28"
Max. Wheel diameter	45"(1143mm)	45"(1143mm)	41"(1040mm)	45"(1143mm)
Max. Wheel width	16"(406mm)	16"(406mm)	14"(355mm)	16"(406mm)
N.W/G.W	532Lb/594Lb (242Kg/270Kg)	559Lb/682Lb (254Kg/310kg)	660Lb/743Lb (310Kg/359Kg)	737Lb/856Lb (335Kg/389kg)
Packing Size	1130*900*1070(mm)	1130*900*1070(mm)	960*760*1070(mm)	900*1130*1070(mm)
Price	\$2395	\$2995	\$3495	\$3995

## Combo Specials:



TC-1291IT + WB-1120 **\$3995** SAVE **\$500** 



TC-1227IT + WB-711 **\$5695** *SAVE* **\$500** 



TC-1297IT + WB-711 **\$6195** *SAVE* **\$500** 



TC-1298IT + WB-711 **\$5195** *SAVE* **\$500** 

## LEVERLESS TIRE CHANGERS

## Leverless Tire Changers



Model #	TC-712A	TC-1295	TC-1239
Description	Leverless tilt arm tire changer	Leverless swing arm tire	Leverless Tire changer with
	with bead blaster and left	changer with left assist	high resolution camera and 8"
	assist arm assembly	arm assembly and lifter	LCD Visualization system
Power supply	110V/60Hz,single phase,	110V/60Hz,single phase,	220V/60Hz,single phase,
	1.5HP Motor	1.5HP Motor	2HP Motor
Air Supply	8-10bar (116-145PSI)	8-10bar (116-145PSI)	8-10bar (116-145PSI)
Rim Clamping (External)	12"-23"	8-28″	10″-30″
Rim Clamping (Internal)	14"-26"	8″-28″	10″-30″
Max. Wheel diameter	45"(1143mm)	45"(1143mm)	49"(1250mm)
Max. Wheel width	16"(406mm)	16"(406mm)	22"(558mm)
N.W/G.W	660Lb/743Lb	715Lb/781Lb	1261Lb/1452Lb
	(310Kg/350Kg)	(320Kg/355kg)	(573Kg/660Kg)
Packing Size	1130*900*1050(mm)	1130*900*980(mm)	1700*1150*1770(mm)
Price	\$4095	\$3995	\$10995

## Accessories & Parts for Tire Chanager



## WHEEL BALANCERS

## Wheel Balancers



Model	WB-511	WB-611	WB-514
Design	Manually input for Car/Light Truck	Semi-Automatic for Car/Light Truck	Fully Automatic for Car/Light Truck
Power Supply	110V/1PH/250W	110V/1PH/250W	110V/1PH/250W
Max. Wheel Weight	154Lbs(70Kg)	143Lbs(70Kg)	143Lbs(70Kg)
Rim Diameter	10"-26"	10"-26"	10"-26"
Rim Width	1.5″-20″	1.5"-20"	1.5″-20″
Balancing Accuracy	+/- 1g	+/- 1g	+/- 1g
Measuring Time	6-9s	6-9s	6-9s
Noise Level	<70dB	<70dB	<70dB
Packing Size	900*700*1170mm	980*700*1111mm	980*800*1290mm
N/G Weight	209Lbs/299Lbs	260Lbs/350Lbs	275Lbs/365Lbs
Price	\$1995	\$2395	\$2995

## Combo Specials:



TC-412 + WB-511 \$3495 SAVE \$500



TC-512B + WB-514 \$5695 SAVE \$500



TC-412A + WB-611 \$4295 SAVE \$500



TC-612B + WB-514 \$5995 SAVE \$500

#### NEW MODEL WHEEL BALANCERS

#### New Model Wheel Balancer







Model	WB-1120	WB-711	WB-1850
Design	Semi-Automatic for Car/Van Wheel	Fully Automatic for Car/Light Truck Wheel	Semi Automatic for Carand Big Truck, Built in wheel lift
Power Supply	110V/1PH/250W	110V/1PH/250W	220V/1PH/550W
Max. Wheel weight	143Lbs(65Kg)	143Lbs(65Kg)	330Lbs(149Kg)
Rim diameter	10"-24"	10"-24"	10"-30" Max. Tire Diameter 33"CarMode/51" Truck
Rim Width	1.5"-20"	1.5″-20″	5.5″-20″
Balancing accuracy	+/- 0.04oz	+/- 0.04oz	1g Car/ 10g Truck
Measuring time	8s	8s	8s
Noise level	<70dB	<70dB	
Packing Size	960*760*1250mm	960*760*1250mm	960*1220*1190"mm
N/G weight	216Lbs/250Lbs	227Lbs/277Lbs	498Lbs/601Lbs
Price	\$2095	\$2695	\$2695

## Accessories & Parts for Wheel Balancer



Fe Adhesive Wheel Balancer Weights 1/4 oz x 12-50 pcs/box \$35 / Set



Quick Clamping Nut with Bowl 40mm - **\$105** 36mm - **\$95** 



Wheel weight plier

\$32

Truck Cone with Flange Set For 40mm/36mm Shaft \$160 / Set



AW-Zn-Clip-on-Weights 0.25oz-50pcs/0.50oz-50pcs/0.75oz-50pcs/ 1.00oz-25pcs/1.25oz-25pcs/1.50oz-25pcs/ 1.75oz-25pcs/2.00oz-25pcs \$110 / Set



Wheel Rim Width Measuring Gauge **\$20** 



Motorcycle Adapter Set \$350 / Set



AW-Coated-Fe-Clip-on-Wheel-Weights 0.250z-50pcs/0.500z-50pcs/ 0.750z-50pcs/1.000z-25pcs/ 1.250z-25pcs/1.500z-25pcs/ 1.750z-25pcs/2.000z-25pcs **\$150 / Set** 



Wheel Cones Set with Truck Flange \$350 / Set



Touchless Motorcycle Adapter Set \$540 / Set

#### TWO POST LIFT AND SMALL SCISSOR LIFT

#### CL-245MP 10,000lbs 2 Post Lift with ETL/CSA Certified Power Pack

- Manual release from two sides and pedal release from one side, self-locking protection device, safe and easy to operate.
- Equip hei limit switch to ensure the lifting height safely, prevent the vehicle roof from damaging.
- Minimum height of the lifting pad is 110mm, easily lift and suitable for low profile cars and Suv's.
- Reliable oil cylinder, adopts chrome-plating honed cylinder and piston rod, with Italian seals on hydraulic rams, ensure long service life
- Passed 115% dynamic test and 150% static test

#### TLT-210AS Launch ETL/ALI Certified 10,000lbs 2 post Lift

- Lift vehicle symmetrically and asymmetrically- Assures maximum service bay efficiency.
- Adjustable Column Height Provides an extra 6" higher
- Stackable Foot Pads Extensions, with the two 6" tall and two 3" short extensions.
- Single Point Lock Release Allows technicians to disengage both column locks simultaneously.
- Heavy Duty Arm Restraint System Oversize rugged steel gears and springs for trouble operation.
- Double Telescoping Screw Pads Used with or without rubber pads offering 6.5" adjustment



N de de l	01 00011	CL C207
Model	CL-S30H	CL-S30Z
Description	Low-Rise Scissor lift	Mid-Rise Scissor lift
Lifting capacity	2500kg (5500Lb)	3000kg(6600Lb)
Lifting height	25"(635mm)	27.6"(700mm)
Platform height	3.7"(95mm)	4.1"(105mm)
Platform length	55"(1400mm)	57" (1450mm)
Platform width	19.7"(500mm)	18.9" (480mm)
Lifting time	≤25s	≤30s
Dropping time	≤25s	$\leq$ 30s
Width	74"(1880mm)	67"(1710mm)
Length	79.7"(2024mm)	80.7"(2050mm)
Warranty	1 Year	1 Year
Price	\$2895	\$3695



Model #	CL-245MP	TLT210-AS
Cl Descriptions	Overhead, 2 post lift	Overhead, 2 post lift
Lifting Capacity	10,000lbs	10,000lbs
Lifting Height	76"(1900mm)	76.4"(1920mm)
Column Height	150"(3810mm)	148.8"(3780mm)
Inside Column Width	101"(2576mm)	110.2"(2800mm)
Drive-Thru Clearance	95"(2414mm)	98.4"(2500mm)
Lifting Speed(S)	≤54s	≤50s
Dropping Speed(S)	≤54s	≤50s
Overall Width	135"(3426mm)	136.6"(3470mm)
Max. Load Per Arm	2750Lbs	2750Lbs
Ceiling Height Required	154" (12.83')	149.5" (12.45')
Narrow Bay Setting	-	Deduct 5.9"(143mm)
Motor	2HP	2HP
Voltage	220V/Single Phase	220V/Single Phase
Warranty	1 Year	1 Year
Price	\$3195	\$3995

#### CL-S30Z Mid-Rise Low Profile Scissor Lift \$3895


- Electro-hydraulic with mid-rise surface mounted, is perfect equipment for tire changing, quick service, etc.
- Low profile platforms, only 105mm high when fully lowered, need less space.
- Pneumatic safety lock is automatically engaged after pressing the up/down button.
- Anti-surge valve prevents the arms from sudden falling in case of broken hydraulic hose for both operator and vehicle's safety.
   Low voltage controls conform to CSA standards

#### CL-S30H Low Rise Portable Small Scissor Lift \$2895


- Electro-hydraulic with mid-rise surface mounted, is perfect equipment for tire changing,quick service, etc.
- Low profile platforms, only 95mm high when fully lowered, need less space.
- Each platform is the complete steel plate without splicing, to ensure flatness and durability.
- With safety rack in each column, mechanical safety lock is automatically engaged during lifting.

## FOUR POST COMMERCIAL LIFT

## CL-455 12,000 lbs Commercial Grade Four Post Lift



#### CL-455A 12,000lbs Commercial Grade Four Post Alignment Lift



Delivery and Installation not included

## FOUR WHEEL ALIGNMENT SYSTEM

#### CL-S55A 12,000lbs Alignment Scissor Lift

Large Platform Scissor Lift for Four Wheel Alignment

- Open front design that provides easy access to alignment service and calibration areas.
- 26" Wide runways provide easy drive-on for large vehicles.
- Hydraulic equalization and full support rear member deliver repeatable smooth level lifting.
- Turntables are adjustable and suitable for different automobile.
- The two Centre Jacks are included for wheel alignment.
- Pneumatic safety lock is automatically engaged after pressing the up/down button.
- Anti-surge valve prevents the arms from sudden falling in case of broken hydraulic hose, for both operator and vehicle's safety.
- Each platform is one piece without welding to ensure flatness and durability.
- Low voltage controls conform to CE standards.




Model	Machine	Lifting	Lifting	Platform	Platform	Platform	Lifting	Dropping	Overall	Overall
	Body	Capacity	Height	Height	Length	Width	Speed	Speed	Width	Length
CL-S55A	Main Unit	12000lb	72.8"	15"	197"	26.4"	≤55	$\leq$ 55	84.3"	216.50"

#### Ultra 3D+ Wheel Aligner

- 20 degree in-turnplate push rolling-out compensation
- Non-stop at push rolling-out compensation
- 10/20 degree non-stop at caster swing
- Camera bar cruise control to follow lift movement automatically, assure 100% full height range measurement (Ultra 3D+)
- Ultra bright target, minimal sunlight abuse
- Vehicle position auto adaptive
- Simplicity and painless at installation
- 4-step calibration (only needed when change camera)
- Two years warranty and two years free update



Ultra 3D Fixed Height, Fixed Column



Ultra 3D+ Camera bar move automatically

#### Declinometer Input





State and State



arget monitoring	🛃 75 (@)75 (@)77 💼 78 🎘 To	-
: ::	2013 B. 24 100 B. 10	
		1
		3

#### Test Result

All test result	L ··· (0)	14 (2)17 (2114 - 2011)
7 2.60°		5 2.70°
<mark>⊁11.80</mark> °		₹12.00°
⊤ 2.28°		🐨 1.66°
/⁼ 4.01°	7*3.07°	-* <b>∵-0.94°</b>
₹ 0.12°	🔽 3.95°	<b>7 0.14°</b>
i <sup>≖</sup> -1.93°	7*4.04°	** 5.97°


Delivery and Installation not included

## **3D WHEEL ALIGNMENT**



## FOUR WHEEL ALIGNMENT SYSTEM

## Alignment Lift and Alignment Machine Combo Special



Delivery and Installation not included







