

Pneumatic Oil Extractor



FEATURES

- Strong vacuum extraction system, fast, safe and easy extract used oil and other fluids out from vehicles.
- Suitable for cars, boats, motorcycles and small engines.
- Equipped with steel probe holder which is never broken and provide safe protection for suction probes.
- Many diameter of probes (included 5mm, 6mm, 7mm, 8mm) made by copper and flexible PVC.
- Dia. 5mm probe and different color probes are optional. Dia. 5mm probe can provide a faster suction speed due to over-thin thickness of the PVC material.
- Power from air compressor, safe and easy operation.

HC -2085 PARAMETERS

> Tank capacity(Liter/US Gallon)	65/17.1
> Air Inlet Pressure(bar/psi)	6-8/87-116
> Air Inlet Connection(inch)	1/4"
> Vacuum Degree(bar)	-1~0
> Air Pressure for Oil Discharge(bar/psi)	0.7~1/10~15
> Oil Temperature Range(°C)	40-60
> Suction Speed@Probe dia. \varnothing 8 & Oil 60 °C(Liter/m/US Gallon/m)	6.5/1.72
> Suction Hose(dia.@length)	\varnothing 19*1.5m
> Draining Hose(dia.@length)	\varnothing 19*1.5m
> Collection Bowl Capacity(Liter/US Gallon)	16/4.2
> Collection Bowl Diameter(mm)	/
> Maximum Height(mm)	/
> Min Height(mm)	/
> Optional Extension Funnel Diameter(mm)	/
> N.W./G.W.(kgs)	18.5/21
> Dimension(mm)	470*440*940

