

## Mobile Waste Oil Suction



- Pneumatic
- Strong vacuum extraction system
- Exclusive patented self-explosion protection device.
- Suitable for cars, motorcycles boats & small engines.

### HC2297 PARAMETERS

> Tank capacity(Liter/US Gallon)	80/21.1
> Air Inlet Pressure(bar/psi)	6~8/87~116
> Air Inlet Connection(inch)	1/4"
> Vacuum Degree(bar)	-1~0
> Air Pressure for Oil Discharge(bar/psi)	0.7 ~ 1/10 ~ 14
> Oil Temperature Range( °C)	40~60
> Suction Speed@Probe dia. ø8 & Oil 60 °C(Liter/m/US Gallon/m)	6.5/1.72
> Modular cylinder capacity (Liter/US Gallon)	9/2.4
> Suction Hose(dia.@length)	G1/2"*2.0m
> Draining Hose(dia.@length)	G1/2"*2.0m
> Collection Bowl Capacity(Liter/US Gallon)	15/4.0
> Collection Bowl Diameter(mm)	400
> Maximum Height(mm)	1650
> Min Height(mm)	1390
> Optional Extension Funnel Diameter(mm)	560
> N.W./G.W.(kgs)	26.2/29.1
> Dimension(mm)	/

