

TC-1239

HIGHER CLASS SERIES 2 years warranty

PROTEC
The Trusted Supplier in Automotive tools and equipment



Protec Equipment Canada

2410 Dunwin Drive, Unit 6&7, Mississauga, ON L5L 1J9

Tel: 905-569-8878 Fax: 905-569-1238

www.protecequipment.ca

- * High resolution camera and 8" VGA LCD visualization system lets operator to monitor and control tyre demounting operation. Imported hydraulic pump station and reverse switch.



- * Full hydraulic combiner pressing disk and nylon pressing roller make tyre and rim detached instantly.
- * Full automatic operation control and clamping rim size 10"-30" are specially suitable for big size tyres, explosion-proof tyre, low profile tyre, RV tyres and big vacuum tyres.
- * 360° rotary tyre pressing help arm.
- * Full-automatic hydraulic 360° rotary steel tyre demounting hook can demount tyre without lever.



SPECIFICATIONS

Rim dimensions	10"~ 30"
Working pressure	8-10bar (116-145 psi)
Hydraulic pressure	100bar
Optional rotating motor power supply	220v (1ph/3ph)/380v(3ph)
Optional pump power motor power supply	220v (3ph)/380v(3ph)
Rotating motor power	0.75/1.1 kw
Pump power	1.5 kw
Bead breaker force	1400kg
N/G weight	573/660 kg(1260.6/1452 lbs)

