



Features

- Upgrade 098 help arm, higher and longer, extends working coverage.
- Quickly demount/mount the tyres saving the working time and improving work efficiency

- Wider and bigger machine cabinet and central positioning flange for 28" rims greatly increase work strength
- Max working scope up to 28"!!!

- 5" plastic demount/mount head, avoiding the metal bird head scratch rims effectively;
- Vertical arm positioning automatically and synchronous pneumatic locked at any optional position

TC-1295



International patent right 098 help arm: simple, reliable and stable

- Nylon pressing roller helps to build a little space 2-3mm between the rim and the bird head, to avoid metal bird head scratch the rim.
- Easy to operate, one man can dismantle big tire easily, such as tyre for BMW 7series

Multi-function left help arm

- 360° rotary tyre pressing help arm, combined tyre pressing head has functions of lifting tyre, pressing tyre and central positioning.
- Central positioning function which can make wheel and turntable in ceter position
- Function of lifting tyre makes it easily to raise the low profile tires, no lever to dismount the down bead



SPECIFICATIONS

Rim dimensions	8" ~ 28"
Max. wheel width	406mm(16")
Max. wheel diameter	1143mm(45")
Working pressure	8-10bar (116-145 psi)
Optional power supply	110v(1ph)/220v(1ph)/380v(3ph)
Optional motor power	0.55/0.75/1.1 kw
Bead breaker force	2500kg
Noise level	<75 dB
Single package overall dimension	1130*900*1050mm(3.7*3.0*3.4 ft)
N/G weight	355/325 kg(715/781 lbs)