## PROTEC



## WB-611B WHEEL BALANCER





## TECHNICAL DATA <<<

| TECHNICAE DAIN     |                              |
|--------------------|------------------------------|
| Motor power        | 110V/220V/380V<br>250W       |
| Max. Wheel weight  | 143Lb(65Kg)                  |
| Rim width          | 1.5"-20"<br>(38mm-508mm)     |
| Rim diameter       | 10"-28"<br>(254mm-610mm)     |
| Balancing accuracy | ±1g                          |
| Measuring time     | 6-9s                         |
| Noise              | <70dB                        |
| N.W./G.W.          | 282Lb/308Lb<br>(128Kg/140Kg) |

Packing size:980×700×1111(mm)

## STANDARD ACCESSORIES <<<



•Double-side 12-point self-calibration, fast and convenient adjustment speed★the software can zero the balance shaft, improve the two clamping★the balance shaft can idle, there is no requirement for tire weight, high precision ★self-calibration of 14-18 tire, 5/10/15 G auto failure analysis★help customer diagnose the problem accurately, repair machine ★ digital tube, LED, brightness adjustment, to cope with all kinds of environment★ optimized G/head conversion, in/MM, indicator clear status ★ high speed, sensitive keys, smooth operation★ increase OPT optimization function ★can be equipped with width scale can be equipped with grating equipment ★software to remove balance axis imbalance, increase the two transposition error ★ according to the weight of the tire automatically add or subtract balance speed.